

# Technical Specification Sheet

JAN 2021, Vol.1

## DOBU Mask Particulate Respirator

The NIOSH approved Doku Mask 201 Series filtering facepiece respirators are designed to help provide respiratory protection against certain airborne contaminants. The respirator shall be used in accordance with the instructions and limitations as well as applicable safety and health regulations.



### INSTRUCTIONS

- ✓ Single Use Only
- ✓ Use for solid particulates and mists in concentrations not exceeding 10X PEL/OEL
- ✓ This respirator helps reduce exposures to certain airborne contaminants
- ✓ Read User Instructions carefully before use
- ✓ Only use the manufacturer's replacement parts as specified

### Key Features

- NIOSH approved N95 rating
- High efficiency HEPA Filter, 3 Layers
- Low Exhaust/Inhalation Resistance
- Double elasticated straps
- Light weight (<0.2oz), 2D Folded Type
- Dimension: H. 5.25" x W. 7.15"
- 100% made in Korea including raw materials provided by qualified supplier's

### Approvals and Standards

- NIOSH approval No.: TC-84A-7851
- NIOSH 42 CFR 84 Class N95 requirements for a min. 95% filtration efficiency
- Cautions and Limitations: ABCJMNOP
- Assigned Protection Factor (APF 10) per US OSHA and MSHA

### State Specific Contract information

- State of California
- State-wide Contract Number: 1-20-65-32p
- Mask, Respirator and Surgical 95 Non-Vented (Standard/Bulk Pricing)



# TECHNICAL SPECIFICATION SHEET



INFOMOVEPPE

## 201 NIOSH® TC-84A-7851

### LIMITATIONS

- ✓ Do NOT use in atmospheres containing less than 19.5% oxygen.
- ✓ Do NOT use for gases and vapors, oil aerosols, asbestos, arsenic, cadmium lead, &c US OSHA has separate substance-specific standards in the Exposure Limits Table
- ✓ Do NOT substitute, alter, add, or remove parts.
- ✓ Immediately leave contaminated area
- ✓ Do NOT use as surgical masks

### Shelf Life and Storage

- 3 years from the date of manufacture
- Use by date on box in YYYY.MM.DD format
- Store respirators in the original packaging, Keep the respirators away from contaminated areas, dust, direct exposure to sunlight, extreme temperatures, excessive moisture, and damaging chemicals
- Store in temperatures between - 4°F (-20°C) and +86°F (+30°C) and never exceeding 80% RH. Assigned Protection Factor (APF 10) per US OSHA
- Always verify that its seal before use

### Packagings

- 500 masks per Box (Individually sealed masks)
- 14,000 masks (28 Boxes) per Pallet

#### Warning – Misuse may result in sickness or death

Before use, carefully read the User Instructions provided as a part of the product packaging.

For correct use, contact supervisor with the User instructions, or call Customer Service Dept. INFOMOVE INT., INC. as below.



### For More Information

Technical Assistance / Customer Service:

Tel 1-714-400-2075

Fax1-714-683-0460

cs@infomove.net

INFOMOVE INTERNATIONAL, INC.

18218 McDermott E STE G IRVINE, CA 92614

Hours of Operation: M-F 8:00 am – 5:00PM (PST)

www.infomoveppe.com

Manufactured by **DOBU MASK**

DOBU Life Tech Co., Ltd  
38-3 Hoean-daero, Maesan-ri, Opo-eup, Gwanju-si,  
Gyeonggi-do, Republic of Korea  
Tel (+82) 31-765-9311  
www.dobumask.com

